

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

5 **Listing of Claims:**

Claim 1 (currently amended): A network interface circuit for transmitting signals to different nodes of a network, the network interface circuit comprising:

a MAC circuit;

10 a first scrambler coupled to the MAC circuit for generating a first transmission signal by executing a logic operation with a first signal and a first scrambling code;

a second scrambler coupled to the MAC circuit for generating a second transmission signal by executing the logical operation with a second signal and a second scrambling code, wherein the first  
15 scrambling code and the second scrambling code are different such that the first transmission signal and the second transmission signal are unlike;

a first transmission port coupled to the first scrambler for transmitting only the first transmission signal to a network node; and  
a second transmission port coupled to the second scrambler for  
20 transmitting only the second transmission signal to another network node.

and

~~two transmission ports for transmitting the first and the second transmission signals to the corresponding network nodes.~~

25

Claim 2 (original): The network interface circuit of claim 1 wherein the first scrambler

comprises a first random number generator for executing a second logic operation with a first seed to generate the first scrambling code, and the second scrambler comprises a second random number generator for executing the second logic operation with a second seed to generate the second scrambling code; wherein the first seed and the second seed are different so that the first scrambling code and the second scrambling code are unlike.

Claim 3 (original): The network interface circuit of claim 2 capable of updating the value of the first seed after a predetermined period after the first scrambler generates the first transmission signal, and capable of updating the value of the second seed after the predetermined period after the second scrambler generates the second transmission signal.

Claim 4 (original): The network interface circuit of claim 3 in which the first scrambler generates the first transmission signal after receiving a first reset signal, and the second scrambler generates the second transmission signal after receiving a second reset signal, wherein the first reset signal and the second reset signal are transmitted to the first scrambler and the second scrambler respectively at different times so that the first scrambler and the second scrambler start to generate the first transmission signal and the second transmission signal respectively at different times.

Claim 5 (original): The network interface circuit of claim 4 capable of setting an initial value to the first seed when the first scrambler receives the first reset signal and another initial value to the second seed when the second scrambler receives the second reset signal.

Claim 6 (currently amended): The network interface circuit of claim 1 further comprising a first encoder and a second encoder for encoding the first transmission signal and

the second transmission signal respectively in the same way, the encoded first transmission signal and the encoded second transmission signal being transmitted to the corresponding network nodes through the ~~two~~ first and second transmission ports, wherein the first encoder and the second encoder encode a signal composed of 0 and 1 values to one composed of 0, 1, and -1 values.

Claim 7 (currently amended): The network interface circuit of claim 1 wherein the first scrambler comprises a first random number generator for executing a second logic operation with a first seed to generate the first scrambling code, and the second  
scrambler comprises a second random number generator for executing the second logic operation with a second seed to generate the second scrambling code; wherein the first seed and the second seed are different elements of a same set of seeds, each element of the set of seeds being utilized by each of the first and the second random number generators in turn. ~~in which the logical operation is exclusive OR.~~

Claim 8 (currently amended): A network interface circuit for transmitting signals to different nodes of a network; the network interface circuit comprising:  
a reset circuit for generating a first reset signal and a second reset signal;  
a first signal circuit coupled to the reset circuit and comprising at least  
a first scrambler and generating a first transmission signal by  
utilizing the first scrambler to execute a logical operation with a  
first signal and a first scrambling code when receiving a first reset  
signal;  
a second signal circuit coupled to the reset circuit and comprising at  
least a second scrambler and generating a second transmission  
signal by utilizing the second scrambler to execute the logical  
operation with a second signal and a second scrambling code when  
receiving a second reset signal;

a first transmission port coupled to the first scrambler for transmitting  
the first transmission signal to a network node; and  
a second transmission port coupled to the second scrambler for  
transmitting the second transmission signal to another network  
5 node.

and

~~two transmission ports for transmitting the first and the second~~  
~~transmission signals to the corresponding network nodes.~~

10 Claim 9 (original): The network interface circuit of claim 8 in which the reset circuits generate the first reset signal and the second reset signal at different times so that the time of the first signal circuit to generate the first transmission signal and the time of the second signal circuit to generate the second transmission signal are not the same.

15 Claim 10 (currently amended): The network interface circuit of claim 8 wherein the first  
scrambler comprises a first random number generator for executing a second logic  
operation with a first seed to generate the first scrambling code, and the second  
scrambler comprises a second random number generator for executing the second  
logic operation with a second seed to generate the second scrambling code; wherein  
20 the first seed and the second seed are different, non-equal elements of a same set of  
seeds utilized by each of the first and the second random number generators. ~~in~~  
~~which the first scrambler and the second scrambler are different so the first~~  
~~transmission signal and the second transmission signal are different even when the~~  
~~first signal is equal to the second signal.~~

25

Claim 11 (currently amended): A method for a network interface circuit to transmit signals to different nodes of a network, the method comprising:  
executing a logical operation with a first signal and a first scrambling code, and

executing the logical operation with a second signal and a second scrambling code, wherein the second scrambling code is different with the first scrambling code so the first transmission signal and the second transmission signals are different even when the first signal is equal to the second signal; and  
5 transmitting the first transmission signal to a node of the network and the second transmission signal to another node ~~the corresponding nodes~~ of the network respectively.

Claim 12 (original): The method of claim 11 in which the first scrambling code is  
10 generated by executing a second logical operation with a first seed and the second scrambling code is generated by executing the second logical operation with a second seed, wherein the first seed and the second seed are different so that the first scrambling code and the second scrambling code are unlike.

15 Claim 13 (original): The method of claim 12 in which the value of the first seed is updated after a predetermined period after the first transmission signal is generated, and the value of the second seed is updated after the predetermined period after the second transmission signal is generated.

20 Claim 14 (original): The method of claim 13 in which the first transmission signal is generated after receiving a first reset signal, and the second transmission signal is generated after receiving a second reset signal, wherein the first reset signal and the second reset signal turn on the process of generating the first scrambling code and the process of generating the second scrambling code at different times, so that the  
25 first transmission signal and the second transmission signal are generated at different times.

Claim 15 (original): The method of claim 14 in which the first seed is set to an initial

value when the first reset signal is received, and the second seed is set to another initial value when the second reset signal is received.

Claim 16 (currently amended): The method of claim 11 capable of encoding the first  
5 transmission signal and the second transmission signal respectively in the same way,  
the encoded first transmission signal and the encoded second transmission signal  
being transmitted to the corresponding network nodes through the two transmission  
ports, the way of encoding is to encode a digital signal composed of 0 and 1 values  
to one composed of 0, 1, and -1 values.

10 Claim 17 (currently amended): The method of claim 11 further comprising:  
generating the first scrambling code according to a first seed number;  
generating the second scrambling code according to a second seed number, the first  
seed and the second seed being different elements of a same set of seeds; and  
15 utilizing each element of the set of seeds to be the first seed number and to be the  
second seed number in turn. in which the —logical operation is exclusive OR.

Claim 18 (currently amended): A method for a network interface circuit to transmit  
signals to different nodes of a network, the method comprising:  
20 receiving a first reset signal and a second reset signal;  
executing a logical operation with a first signal and  
a first scrambling code to generate a first transmission signal right after receiving  
the first reset signal, and executing the logical operation with a second signal  
and a second scrambling code to generate a second transmission signal right  
25 after receiving the second reset signal, wherein the second transmission signal  
are different from the first transmission signal; and  
transmitting the first transmission signal to a first node of the network and the  
second transmission signal to another node of the corresponding nodes in the

network respectively.

Claim 19 (original): The method of claim 18 generating the first reset signal and the  
second reset signal at different times respectively so that the times to generate the  
5 first transmission signal and the second transmission signal are different.

Claim 20 (original): The method of claim 19 further comprising:

generating the first scrambling code according to a first seed number;

generating the second scrambling code according to a second seed number, the first  
10 seed and the second seed being different, non-equal elements of a same set of  
seeds; and

utilizing each element of the set of seeds to be the first seed number and to be the  
second seed number in turn. ~~in which the first scrambling code and the second~~  
~~scrambling code are different so that the first transmission signal are not equal~~  
15 ~~to the second transmission signal even when the first signal and the second~~  
~~signal are the same.~~